



IRIS COLOR SRL
Via Cechov, 3
San Giuliano Milanese
20098 (MI) Italy
Tel / Fax +39 02 9841633
amministrazione@iriscolor.eu



Riccione

TECHNICAL DATA SHEET **MODENA**

DESCRIPTION

Highly versatile and easily designable decorative plaster for creating an unlimited variety of textured effects that can also be completed with any multicolor finish of your choice

INTENDED USE

For interiors, on rendered walls, plasters, plasterboards, gypsum, wood etc. appropriately treated.

BASE PREPARATION

Surface to treat must be sound, dry, clean and free from any loose friable material.
On new or old walls one coat of the Riccione Professional Primers is recommended.

APPLICATION

Brush, roller or inox trowel

TECHNICAL DATA

<i>Spreading rate (sq.m./l) (per coat)</i>	Highly variable according to the effect to be created
<i>Thinning</i>	Ready to use
<i>Drying at 25°C</i>	4-6 hours, touch dry
<i>Recoating time</i>	12 hours
<i>Specific weight (Kg/l)</i>	~ 1.60
<i>VOC - Directive 2004/42/CE (g/l)</i>	26; cat L BA max limit 200

ADIVICES

Do not use at temperatures below 5°C. Clean the tools with soap and water. Fears the frost. Keep in a cold and dry place.