



IRIS COLOR SRL
 Via Cechov, 3
 San Giuliano Milanese
 20098 (MI) Italy
 Tel / Fax +39 02 9841633
 amministrazione@iriscolor.eu



Riccione

TECHNICAL DATA SHEET **NAPOLI**

DESCRIPTION

Fleck based decorative wall finish. Available in White or Metallic bases as follows:

WHITE
SILVER
GOLD
COPPER

INTENDED USE

Any paintable interior wall surface.

BASE PREPARATION

Surface to treat must be sound, dry, clean and free from any loose friable material. On new or old walls one coat of the Riccione Professional Primers is recommended.

A basecoat of PAINT PRIMER in either white or colored, according to the color to be applied and the effect desired, is always recommended.

APPLICATION

Spalter brush.

After about 10-15 minutes from application, when the product has just started to dry, the flecks can be flattened with a soft plastic spatula.

TECHNICAL DATA

<i>Spreading rate (sq.m./l) (per coat)</i>	About 8 to 10 sq.m. each liter
<i>Thinning</i>	max 5% water
<i>Drying at 25°C</i>	4-6 hours, touch dry (1 day, thoroughly dry)
<i>Specific weight (Kg/l)</i>	~ 1.020
<i>VOC - Directive 2004/42/CE (g/l)</i>	10; cat L BA max limit 200

ADIVICES

Do not use at temperatures below 5°C. Clean the tools with soap and water. Fears the frost. Keep in a cold and dry place.