



**IRIS COLOR SRL**  
Via Cechov, 3  
San Giuliano Milanese  
20098 (MI) Italy  
Tel / Fax +39 02 9841633  
amministrazione@iriscolor.eu



**Riccione**

**TECHNICAL DATA SHEET**  
**VENEZIA**

## DESCRIPTION

Decorative waterborne paint for interiors that allows you to easily and quickly obtain a high quality, glossy finish with the look of the world famous Venetian polished plaster

## INTENDED USE

Any paintable interior wall.

## BASE PREPARATION

Surface to treat must be sound, dry, clean and free from any loose friable material.  
On new or old walls one coat of the Riccione Professional Primers is recommended.

## APPLICATION

Brush and inox trowel.

## TECHNICAL DATA

<i>Spreading rate (sq.m./l) (per coat)</i>	About 6 to 8 sq.m. per liter
<i>Thinning</i>	Ready to use
<i>Drying at 25°C</i>	3-4 hours, touch dry
<i>Recoating time</i>	6-8 hours
<i>Specific weight (Kg/l)</i>	~ 1.750
<i>VOC - Directive 2004/42/CE (g/l)</i>	19; cat L BA max limit 200

## ADIVICES

Do not use at temperatures below 5°C. Clean the tools with soap and water. Fears the frost. Keep in a cold and dry place.